

PRODUCT DATA SHEET

TARKETT TOUCH

JANUARY 2016

Type of flooring

EN ISO 26986

Vinyl Floorcovering

Class of use

EN ISO 10874



23



32

Class

Description



ISO 24346

Total thickness

2,50 mm



EN ISO 24340

Wear Layer thickness

0,50 mm



EN ISO 24341

Length + Width

25 m

4+3+2m



EN ISO 23997

Mass per Unit Area

2,500 kg/m²

ISO 11638

Wear-layer binder content

Type I



ISO 4918

Castor Chair

No damage



EN ISO 717/2

Impact sound insulation

12 dB



EN ISO 24343-1

Residual indentation

≤ 0,20 mm

Other Characteristics



ISO 105/B02

Light fastness

≥ 6



Slip resistance

EN 13893

DIN 51130

μ ≥ 0,30

R10



Fire Classification

EN 13501-1

glued on wooden panel

glued on cement

Cfl-s1

Bfl-s1



EN ISO 23999

(Previously EN 434)

Dimensional stability

≤ 0,10 %



Recyclable

OK



EN 1815

Static electrical propensity

≤ 2 kV



EN ISO 10456

(EN 12524)

Thermal resistance for underfloor heating

0,02 m²/kW



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.