






BRAVO



PAVITEX

Italiano	English	Français	Deutsch		
Pavimentazione agugliata	Needle punched carpet	Tapis aiguillete	Nadelvlies Teppichboden		BRAVO
Dati di fabbricazione	Technical data	Caracteristiques techniques	Technische Daten		
Dimensione rotoli standard	Standard rolls dimensions	Dimensions standard des rouleaux	Rollen abmessungen		40 m x 2 m
Composizione della fibra dello strato di utilizzo	Fiber composition of use surface	Composition fibreuse de la couche d'usage	Faserzusammensetzung der Nutschicht		80% PA + 20% PP
Tipo di dorso	Backing	Enduction d'envers	Rücken		Latex
Massa areica totale	Total mass per unit area	Masse totale par unité de surface	Flaechengewicht		900 gr/m²
Spessore totale	Total thickness	Épaisseur totale	Gesamtdicke		3,6 mm
Carica elettrostatica	Body voltage	Essai du marcheur	Koeperspannung		<2,0 kV
Assorbimento acustico	Sound absorption	Performance acoustique	Trittschalldämmung		17 dB
Comportamento alla fiamma	Flammability	Réaction au feu	Brandverhalten		EN 13501
Posa Incollaggio totale	Installation Adhesive bonded	Pose Pose collée en plein	Verlegen Vollflaechige Klebung		
Impiego Magazzini Scuole Uffici	Uses Stores Schools Offices	Utilisation Magasins Ecoles Bureaux	Verwendungsbereich Kaufhäuser Schulen Büros	rev. 2 04-03 