



Italiano	English	Français	Deutsch		
Pavimentazione agugliata	Needle punched carpet	Tapis aiguillete	Nadelvlies Teppichboden	ISO 2424	CIAO
Dati di fabbricazione	Technical data	Caracteristiques techniques	Technische Daten		
Dimensione rotoli standard	Standard rolls dimensions	Dimensions standard des rouleaux	Rollen abmessungen	ISO 3018	40 m x 2 m
Composizione della fibra dello strato di utilizzo	Fiber composition of use surface	Composition fibreuse de la couche d'usage	Faserzusammensetzung der Nutschicht	Dir. 96/73 CE	60% PA + 40% PP
Composizione supporto	Back layer	Couche d'envers	Traeger		100% sintetico
Tipo di dorso	Backing	Enduction d'envers	Rücken	ISO 2424	Latex
Massa areica totale	Total mass per unit area	Masse totale par unité de surface	Flächengewicht	ISO 8543	850 gr/m <sup>2</sup>
Spessore totale	Total thickness	Épaisseur totale	Gesamtdicke	ISO 1765	3,7 mm
Carica elettrostatica	Body voltage	Essai du marcheur	Koerperspannung	EN 1815	< 2,0 kV
Assorbimento acustico	Sound absorption	Performance acoustique	Trittschalldämmung	ISO 140/8	17 dB
Traffico	Suitability	Professionel moyen	Beanspruchungsbereich	EN 1307	Classe 3
Comportamento alla fiamma	Flammability	Réaction au feu	Brandverhalten	EN 13501-1 D.M. 26.06.84	Cfl - s1 Classe 1
Posa Incollaggio totale	Installation Adhesive bonded	Pose Pose collée en plein	Verlegen Vollflächige Klebung		
Impiego Uffici privati Sale d'attesa Reception	Uses Private offices Waiting rooms Receptions	Utilisation Bureaux usage personel Salles d'attente Réception	Verwendungsbereich Büroräume Warteräume Hallen	rev. 1 04/03	

Strapazierwert				Komfortwert			
en	strank	normal	gering	einfach	gut	hoch	luxurios

