

Declaration of Performance



No. GFL TN – DoP - 0182

1.	<p><i>Unique identification code of the product type:</i></p> <p>Green-Flor® Tierra Nueva</p>																																			
2.	<p><i>Type, batch or serial number or any other element following identification of construction product as required pursuant to article 11(4):</i></p> <p>Batch number: See box of the product</p>																																			
3.	<p><i>Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:</i></p> <p>Flooring for indoor use</p>																																			
4.	<p><i>Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to article 11(5):</i></p> <p>G. T. Floor Co.Ltd, No.162, Xin Sheng Road, Taishan District, 24341 Taipei County, TAIWAN R.O.C.</p>																																			
5.	<p><i>Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):</i></p> <p>G. T. Floor Co.Ltd, No.162, Xin Sheng Road, Taishan District, 24341 Taipei County, TAIWAN R.O.C.</p>																																			
6.	<p><i>System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:</i></p> <p>System 3</p>																																			
7.	<p><i>In case of the declaration of performance concerning a construction product covered by a harmonised standard:</i></p> <p>The ÖTI – Institut für Ökologie, Technik und Innovation GmbH Notified Body : 0534 has performed the type testing concerning the fire behaviour under system 3 and issued following: Test-Report No.64878</p>																																			
8.	<p>Declared performance</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 35%;">Essential characteristics</th> <th style="width: 20%;">Performance</th> <th style="width: 45%;">Harmonized technical specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire</td> <td style="text-align: center;"></td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Content an Pentachlorophenol</td> <td style="text-align: center;"></td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Formaldehyde Emissions</td> <td style="text-align: center;"></td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Slip resistance</td> <td style="text-align: center;"></td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Slip resistance</td> <td style="text-align: center;">R10</td> <td>DIN 51130, 06/2004</td> </tr> <tr> <td>Electrical behaviour (dissipative)</td> <td style="text-align: center;">NPD</td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Electrical behaviour (conductive)</td> <td style="text-align: center;">NPD</td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Electrical behaviour (antistatic)</td> <td style="text-align: center;">0.1 kV</td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Thermal conductivity [W/mK]</td> <td style="text-align: center;">0,019 m2 K/W</td> <td>EN 14041: 2004/AC:2006</td> </tr> <tr> <td>Water-tightness</td> <td style="text-align: center;">NPD</td> <td>EN 14041: 2004/AC:2006</td> </tr> </tbody> </table>			Essential characteristics	Performance	Harmonized technical specification	Reaction to fire		EN 14041: 2004/AC:2006	Content an Pentachlorophenol		EN 14041: 2004/AC:2006	Formaldehyde Emissions		EN 14041: 2004/AC:2006	Slip resistance		EN 14041: 2004/AC:2006	Slip resistance	R10	DIN 51130, 06/2004	Electrical behaviour (dissipative)	NPD	EN 14041: 2004/AC:2006	Electrical behaviour (conductive)	NPD	EN 14041: 2004/AC:2006	Electrical behaviour (antistatic)	0.1 kV	EN 14041: 2004/AC:2006	Thermal conductivity [W/mK]	0,019 m2 K/W	EN 14041: 2004/AC:2006	Water-tightness	NPD	EN 14041: 2004/AC:2006
Essential characteristics	Performance	Harmonized technical specification																																		
Reaction to fire		EN 14041: 2004/AC:2006																																		
Content an Pentachlorophenol		EN 14041: 2004/AC:2006																																		
Formaldehyde Emissions		EN 14041: 2004/AC:2006																																		
Slip resistance		EN 14041: 2004/AC:2006																																		
Slip resistance	R10	DIN 51130, 06/2004																																		
Electrical behaviour (dissipative)	NPD	EN 14041: 2004/AC:2006																																		
Electrical behaviour (conductive)	NPD	EN 14041: 2004/AC:2006																																		
Electrical behaviour (antistatic)	0.1 kV	EN 14041: 2004/AC:2006																																		
Thermal conductivity [W/mK]	0,019 m2 K/W	EN 14041: 2004/AC:2006																																		
Water-tightness	NPD	EN 14041: 2004/AC:2006																																		
<p><i>The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4</i></p> <p><i>Signed for and on behalf of the manufacturer by:</i></p> <p>Peter Lin, Managing Director G. T. Floor Co.Ltd.</p> <p>Taipei, 15th December 2018</p> <div style="text-align: right; margin-top: 10px;"> </div>																																				